

#158 HIGH TANK TOILET

Installation Instructions

The #158 HIGH TANK TOILET is shipped in 3 cartons.

Carton A: #2-802WH	Toilet bowl with spud installed (2" x 1¼")
Carton B: #T/2-412WH	Toilet tank and cover with trim bag which includes float valve, float ball, float rod, flush valve and rubber flapper.
Carton C: #HTT	Trim kit for high tank toilet includes:
	White plastic nut
#5568	Flush pipe (1¼" x 72")
#5569	Straight supply pipe (½" OD x 72")
#5552	Slip nut (1½" x 1¼")
#5567	Wall bracket (1¼") with 2 brass screws
#5570	Flush elbow assembly with 2 slip nuts and washers
#5560	Spud reducer (2" x 1½") with rubber washer
#413-HA	Tank handle assembly

Tools Needed

Hacksaw or tube cutter – Phillips screwdriver – Level – ¼" drill bit – Wrench
Wax ring seal or plumbers putty – Large screws or toggle bolts

1. Shut off water supply, disconnect plumbing and remove existing toilet bowl.
2. Install **#413-HA** tank handle assembly with chain to tank. Remove handle screw with Phillips screwdriver and remove handle. Remove the front of the trim ring by turning clockwise (this is a left-hand thread). Place assembly through the tank with the washer on assembly (this should be inside the tank). Assemble front trim ring by turning counter clockwise. Put handle on spindle and attach with screw.
3. Using new wax ring seal (not furnished), or plumbers putty, mount the toilet bowl to the floor drain opening.
4. To attach the tank to the wall, locate and drill holes in the wall approximately 80" above the floor. The holes should be 8" center to center. You may choose any height between 75" and 82" and later trim the flush pipe assembly. Use proper hardware to attach the tank to the wall. Large screws, toggle bolts, or other fasteners can be used depending on the wall material. These parts are not furnished. A small spacer should be placed between the wall and tank to allow the tank lid to fit flush with the front of the tank. The spacer is not furnished. Attach tank to wall and use level to check for evenness.
5. Slide the #5552 slip nut up #5568 flush pipe and connect the slip nut to the #5560 outlet at the bottom of the tank. Do not forget the washers.
6. Place #5567 wall bracket against the wall at the height where the lip of the toilet seat cover will come in contact with the bracket. Tighten the 2 brass screws that are furnished and insert them into the wall bracket and attach to the wall.
7. Insert #5570 flush elbow into the toilet bowl taking care to use rubber washers and slip nuts. Do not damage washer or slip nut.
8. Insert #5569 supply pipe into tank and tighten carefully using white plastic nut.
9. Install toilet seat (not furnished).

