

INSTALLTION OF (RMC-22" TRIM) & (RMC-30" TRIM) CONSOLE SINK SUPORT STANDS

Included In The RMC-22" & RMC-30" Console Boxes:

- 2 pcs. Tubing (A) Vertical Floor Support
- 1 pcs. Tubing (B) Horizontal Front Cross Support
- 2 pcs. Tubing (C) Horizontal Side Cross Support
- 2 pcs. 4-Way Right Angle Tee Connectors w/ Set Screws
- 2 pcs. Floor Stand Support Flanges w/ Set Screws
- 6 pcs. Floor Mounting Support Flange Screws
- 2 pcs. Wall Mounted Support Flange w/ Set Screws
- 6 pcs. Wall Mounting Support Flange Screws

Not Included In Console Package:

Sink Wall Mounting Bracket Supports (Provided With Sinks)

INSTALLTION OF CONSOLE SINK SUPPORT STANDS:

- 1 Confirm and inspect all Console Sink Support Stand parts.
Confirm the "Wall Attachment Plate" for supporting the Sink Wall Mounting Bracket Support (provided with sink) and Console Flange Wall Bracket Supports are located at the desired heights and locations. Standard top of sink heights are 33" AFF.
- 2 Starting with Vertical Support Tubes (A) 31" length. Attach both Console Floor Flanges to the plain ends of each tube and tighten. Slide the plugged rubber end of the tubes through the straight ports of the 4-Way Right Angle Tees, alien the centerline heights of tube ports (C) and fasten tight.
Note: 31" Vertical Support Tubes (A) can be trimmed to your desired sink height. Tubing cutter is required to trim tubing.
- 3 **(22" Trim)** Cut Front Horizontal Cross Support Tube (B) to 15 ½" length, insert tube ends into each Right Angle Tee Port and fasten tight.
(30" Trim) Cut Front Horizontal Cross Support Tube (B) to 23 ½" length, insert tube ends into each Right Angle Tee Port and fasten tight.
- 4 **(22" Trim)** Cut Side Horizontal Cross Support Tubes (C) to 14 ½" lengths, insert tube ends into each Right Angle Tee port and Wall Flanges fasten tight. Secure to wall backing plate.
(30" Trim) Cut Side Horizontal Cross Support Tubes (C) to 16 ¼" lengths; insert tube ends into each Right Angle Tee port and Wall Flanges fasten tight. Secure to wall backing plate.
- 5 Place the assembled Console Sink Support Stand against the wall in the desired location mark locations of the Console Floor Flanges and Wall Flanges fasting screws. Remove the Console Sink Support Stand and drill the floor and wall. Reset the assembled Console Sink Support Stand and secure the Console Floor Flanges and Wall Mounted Flanges to the floor, and wall backing plate.

INSTALLTION OF SINK:

- 1 Once sink height is confirmed mark and install the Sink Wall Support Bracket at the desired height and location and secure to Wall Attachment Plate.
- 2 Set sink down onto the Console Sink Support Stand and slide down onto the Sink Wall Support Bracket.
- 3 Apply, Firm-Even-Down Pressure onto the top/back of the sink and into the Sink Wall Support Bracket to secure tight against wall.