

Two Piece Toilet Install

Installation

1. Mark on the floor a line 12" off the finished back wall out to the centerline of the new 4"Ø floor drain.
2. After completing the floor drain, connect the Toilet Floor Flange (22) to the new drain pipe and rotate to the correct position. Attach the two (2) Flange Bolts (13) onto the Toilet Floor Flange (22). Press new Wax Ring Seal (12) onto the toilet bowl outlet connection.
3. Set the toilet down onto the floor while passing the Fl. Flg. Mounting Bolts (13) through the holes in the base of the bowl. Firmly press the toilet bowl down onto the Toilet Floor Flange (22) while using a easy rotational movement to set the bowl down onto the finished floor.
4. Install the Snap-On Bolt Cap Base (14), Metal Washers (15), Hex Head Nuts (16) and tighten snugly until toilet is secure to the floor. Place the Bolt Snap Caps (20) onto the Snap-On Bolt Cap Base (14) and lock.
5. Mounting the toilet tank onto the toilet bowl; Insert the Tank Support Bolts (9), Water Tank Seal (10) and Water Tank Support Nuts (11) through the toilet and tighten. Slip the Water Tank Tapered Gasket (29) onto the flush outlet. When setting the toilet, Insert the Tank Support Bolts (9), and Water Tank Tapered Gasket (29) into the toilet and secure.
6. Install the Water Supply Valve (18). Connect the Water Supply (19) to the Flush Valve (4) connection with supplied nut. Connect the plain end of the Water Supply (19) to the Water Supply Valve (18).

