

| NO. | DESCRIPTION | Q'TY | NO. | DESCRIPTION | Q'TY |
|-----|-------------------|------|-----|---------------|------|
| G1 | SPOUT | 1 | G18 | VALVE BODY | 2 |
| G2 | POP-UP ROD KNOB | 1 | G19 | CONNECT HOSE | 2 |
| G3 | POP-UP ROD | 1 | G20 | CONE WASHER | 2 |
| G4 | SPOUT BASE O-RING | 1 | G21 | LOCK NUT 1/2" | 2 |
| G5 | O-RING | 2 | G22 | DRAIN FACE | 1 |
| G6 | SPOUT FIT WASHER | 1 | G23 | POP-UP FLANGE | 1 |
| G7 | SPOUT LOCK NUT | 1 | G24 | DRAIN BODY | 1 |
| G8 | CONNECT TEE | 1 | G25 | BALL WASHER | 2 |
| G9 | LEVER HANDLE | 2 | G26 | PIVOT ROD | 1 |
| G10 | SET SCREW | 1 | G27 | LOCK NUT | 1 |
| G11 | ALLEN WRENCH | 2 | G28 | SPRING CLIP | 1 |
| G12 | HANDLE BASE | 2 | G29 | ROD STRAP | 1 |
| G13 | RUBBER WASHER | 2 | G30 | SCREW | 1 |
| G14 | PLASTIC WASHER | 2 | | | |
| G15 | BODY LOCK NUT | 2 | | | |
| G16 | HOT CARTRIDGE | 1 | | | |
| G17 | COLD CARTRIDGE | 1 | | | |

Pre-assembly:

- Before beginning installation, use the parts list above to identify each of the components included.

Care: Clean faucet with soapy water and a soft cloth or sponge. Rinse thoroughly with water. Wipe dry. Drying immediately after use helps prevent lime deposits from forming. To protect the finish, do not use abrasive agents or harsh cleansers. If using a cleaning agent, it is best to first test on a small inconspicuous spot before applying solution to entire faucet.

Tel : (800)-444-5969

www.cheviotproducts.com

